IN THE CLAIMS

Please amend the claims as follows:

Claim 1 (currently amended): A packet transmission method for transmitting packets classified according to a quality of service (QoS) requirement from a transmitting node to a receiving node, the packet transmission method comprising the steps of:

in the transmitting node,

selecting sequentially a QoS class;

dividing a queued packet to be transmitted, which belongs ~~belonging~~ to the selected class, into a plurality of predetermined data units[[,]]; ~~and~~

transmitting one of the predetermined data units; and

applying a transmitter-side retransmission control process to the data unit to be transmitted when the selected class is a QoS class specified for data type packets;

in the receiving node,

receiving sequentially the data unit transmitted from the transmitting node;

applying a receiver-side retransmission control process to the received data unit to be assembled when the received data unit belongs to one of the QoS classes specified for the data type packets; and

assembling a plurality of received data units to ~~decompress~~ restore an [[the]] original packet in each QoS class.

Claim 2 (currently amended): The packet transmission method as claimed in claim 1, wherein:

in the step of dividing, the queued packet to be transmitted is divided into a plurality of the data units only when there is no data unit which is not yet transmitted and belongs to the same QoS class as the queued packet to be transmitted.

Claim 3 (currently amended): The packet transmission method as claimed in claim 1, wherein:

in the step of dividing, the queued packet to be transmitted is divided into a plurality of the data units and stored; and

in the step of transmitting, one of the data units belonging to the selected class from the stored data units is transmitted.

Claim 4 (original): The packet transmission method as claimed in claim 1, wherein:

the transmitting node applies a header compression process to the queued packet to be transmitted in a predetermined manner, and divides the header-compressed packet into a plurality of the predetermined data units; and

the receiving node applies to the assembled packet a header decompression process corresponding to the header compression process.

Claim 5 (original): The packet transmission method as claimed in claim 2, wherein:

the transmitting node applies a header compression process to the queued packet to be transmitted in a predetermined manner, and divides the header-compressed packet into a plurality of the predetermined data units; and

the receiving node applies to the assembled packet a header decompression process corresponding to the header compression process.

Claim 6 (original): The packet transmission method as claimed in claim 3, wherein:

the transmitting node applies a header compression process to the queued packet to be transmitted in a predetermined manner, and divides the header-compressed packet into a plurality of the predetermined data units; and

the receiving node applies to the assembled packet a header decompression process corresponding to the header compression process.

Claim 7 (currently amended): A packet transmission system for transmitting packets

classified according to a QoS requirement from a transmitting node to a receiving node,

wherein,

the transmitting node comprises:

a dividing part provided for each of QoS classes for dividing a packet to be

transmitted into a plurality of predetermined data units in each of QoS classes;

a transmitter-side retransmission control part for applying a transmitter-side

retransmission control process in each QoS class to the data unit that belongs to one of QoS

classes specified for data type packets and is one of the data units obtained from the dividing

part; and

a scheduling part for selecting a data unit to be transmitted from a set of data

units including a data unit that belongs to one of QoS classes [[not]] specified for data type

real time packets and is obtained from the dividing part, and a data unit that belongs to one of

the QoS classes specified for data type packets and is obtained from the transmitter-side

retransmission control part, and for transmitting the selected data unit, and

the receiving node comprises:

a receiver-side retransmission control part for applying a receiver-side

retransmission control process in each QoS class to the data unit that belongs to one of the

QoS classes specified for data type packets and is one of the received data units;

an assembling part for assembling in each QoS class [[the]] some data units of

the received data units, which [[that]] belong to one of the QoS classes [[not]] specified for

data type real time packets and are some of the received data units, and the data units

obtained from the receiver-side retransmission control part, which [[that]] belong to one of

the QoS classes specified for data type packets, and are obtained from the receiver-side

retransmission control part in order to decompress restore an [[the]] original packet.

6

Claim 8 (currently amended): The packet transmission system as claimed in claim 7, wherein:

the transmitting node further comprises a header compressing part for applying a header compression process in a predetermined manner to the packet to be transmitted;

the receiving node further comprises a header decompression part;

the dividing part divides a header-compressed packet obtained from the header compressing part into a plurality of the predetermined data units;

the assembling part applies the assembling process to the plurality of the predetermined data units to decompress the header-compressed packet; and

the header decompression part applies a header decompression process, which corresponds ~~corresponding~~ to the header compression process in the header compressing part, to the header-compressed packet obtained from the assembling part in order to ~~decompress~~ restore an [[the]] original packet.

Claim 9 (currently amended): A packet transmission system for transmitting packets classified according to a QoS requirement from a transmitting node to a receiving node, wherein,

the transmitting node comprises:

a first pre-scheduling part for selecting classes having high priority for transmission from QoS classes specified for data type packets;

a second pre-scheduling part for selecting classes having high priority for transmission from QoS classes [[not]] specified for ~~data type~~ real time packets;

a first dividing part for dividing a queued packet to be transmitted, which belongs ~~belonging~~ to the QoS class selected by the first pre-scheduling part, into a plurality of predetermined data units;

a second dividing part for dividing a queued packet to be transmitted, which belongs belonging to the QoS class selected by the second pre-scheduling part, into a plurality of the predetermined data units;

a transmitter-side retransmission control part for applying a transmitter-side retransmission control process to the packet to be transmitted to be divided by the first dividing part; and

a scheduling part for selecting either one of the QoS classes specified for data type packets or one of the QoS classes [[not]] specified for data type real time packets to be transmitted, for transmitting the data unit obtained from the transmitter-side retransmission control part when the QoS class specified for data type packets is selected, and for transmitting the data unit obtained from the second dividing part when the QoS class [[not]] specified for data type real time packets is selected, and

the receiving node comprises:

a receiver-side retransmission control part for applying a receiver-side retransmission control process in each QoS class to the data unit that belongs to one of the QoS classes specified for data type packets and is one of the received data units; and

an assembling part for assembling in each QoS class some [[the]] data units of the received data units, which [[that]] belong to one of the QoS classes [[not]] specified for data type real time packets and are some of the received data units, and the data units obtained from the receiver-side retransmission control part, which [[that]] belong to one of the QoS classes specified for data type packets and are obtained from the receiver-side retransmission control part in each QoS class, in order to decompress restore an [[the]] original packet.

Claim 10 (currently amended): The packet transmission system as claimed in claim 9, wherein:

the transmitting node further comprises a header compressing part for applying a header compression process in a predetermined manner to the packet to be transmitted;

the receiving node further comprises a header decompression part;

the dividing part divides a header-compressed packet obtained from the header compressing part into a plurality of the predetermined data units;

the assembling part applies the assembling process to the plurality of the predetermined data units in order to decompress the header-compressed packet; and

the header decompression part applies a header decompression process, which corresponds corresponding to the header compression process in the header compressing part, to the header-compressed packet obtained from the assembling part in order to decompress restore an [[the]] original packet.

Claim 11 (currently amended): A packet transmission system for transmitting packets classified according to a QoS requirement from a transmitting node to a receiving node, wherein,

the transmitting node comprises:

a first scheduling part for determining transmission order for packets to be transmitted;

a dividing part provided for each QoS class for dividing the packet to be transmitted, of which transmission order is determined by the first scheduling part, into a plurality of predetermined data units in QoS class;

a transmitter-side retransmission control part for applying a transmitter-side retransmission control process in each QoS class to the data unit that belongs to one of QoS classes specified for data type packets and is one of the data units obtained from the dividing part; and

a scheduling part for selecting a data unit to be transmitted from a set of data units including a data unit that belongs to one of QoS classes [[not]] specified for ~~data type~~ real time packets and is obtained from the dividing part, and a data unit that belongs to one of the QoS classes specified for data type packets and is obtained from the transmitter-side retransmission control part, and for transmitting the selected data unit, and

the receiving node comprises:

a receiver-side retransmission control part for applying a receiver-side retransmission control process ~~in each QoS class~~ to the data unit that belongs to one of the QoS classes specified for data type packets and is one of the received data units;

an assembling part for assembling in each QoS class [[the]] some data units of the received date units, which [[that]] belong to one of the QoS classes [[not]] specified for ~~data type~~ real time packets ~~and are some of the received data units~~, and the data units obtained from the receiver-side retransmission control part, which [[that]] belong to one of the QoS classes specified for data type packets ~~and are obtained from the receiver-side retransmission control part~~, in order to ~~decompress~~ restore an [[the]] original packet.

Claim 12 (currently amended): The packet transmission system as claimed in claim 11, wherein:

the transmitting node further comprises a header compressing part for applying a header compression process in a predetermined manner to the packet to be transmitted;

the receiving node further comprises a header decompression part;

the dividing part divides a header-compressed packet obtained from the header compressing part into a plurality of the predetermined data units;

the assembling part applies the assembling process to the plurality of the predetermined data units in order to decompress the header-compressed packet; and

the header decompression part applies a header decompression process, which

corresponds ~~corresponding~~ to the header compression process in the header compressing part,

to the header-compressed packet obtained from the assembling part in order to ~~decompress~~

restore an [[the]] original packet.

Claim 13 (currently amended): A packet transmitting/receiving apparatus comprising

a transmitting part and a receiving part for transmitting and receiving the packets classified

according to a QoS requirement respectively, wherein,

the transmitting part comprises:

a dividing part provided for each QoS class for dividing a packet to be

transmitted into a plurality of predetermined data units in each QoS class;

a transmitter-side retransmission control part for applying a transmitter-side

retransmission control process ~~in each QoS class~~ to the data unit that belongs to one of QoS

classes specified for data type packets and is one of the data units obtained from the dividing

part; and

a scheduling part for selecting a data unit to be transmitted from a set of data

units including a data unit that belongs to one of QoS classes [[not]] specified for ~~data type~~

real time packets and is obtained from the dividing part, and a data unit that belongs to one of

the QoS classes specified for data type packets and is obtained from the transmitter-side

retransmission control part, and for transmitting the selected data unit,

the receiving part comprises:

a receiver-side retransmission control part for applying a receiver-side

retransmission control process ~~in each QoS class~~ to the data unit that belongs to one of the

QoS classes specified for data type packets and is one of the received data units;

an assembling part for assembling in each of QoS classes [[the]] some data

units of the received data units, which [[that]] belong to one of the QoS classes [[not]]

11

specified for ~~data type~~ _real time_ packets ~~and are some of the received data units~~, and the data

units _obtained from the receiver-side retransmission control part, which_ [[that]] belong to one

of the QoS classes specified for data type packets ~~and are obtained from the receiver-side~~

~~retransmission control part,_ in order_ to ~~decompress~~ _restore an_ [[the]] original packet,

the receiver-side retransmission control part generates a retransmission request

control signal to indicate a data unit requested to be retransmitted to another packet

transmitting/receiving apparatus communicating with the packet transmitting/receiving

apparatus,

the scheduling part performs a scheduling process on the retransmission

request control signals with the data unit to be transmitted,

the transmitting part further comprises:

a classifying part for classifying and outputting the retransmission request

control signals transmitted from the opposing packet transmitting/receiving apparatus into the

transmitter-side retransmission control part, and

the transmitter-side retransmission control part outputs to the scheduling part

the data unit indicated by the retransmission request control signal transmitted from the

opposing packet transmitting/receiving apparatus upon the retransmission request control

signal being input.

Claim 14 (currently amended): The packet transmitting/receiving apparatus as

claimed in claim 13, wherein:

the transmitting part further comprises a header compressing part for applying a

header compression process in a predetermined manner to the packet to be transmitted;

the receiving part further comprises a header decompression part;

the dividing part divides a header-compressed packet obtained from the header

compressing part into a plurality of the predetermined data units;

the assembling part applies the assembling process to the plurality of the predetermined data units <u>in order</u> to decompress the header-compressed packet; and

the header decompression part applies a header decompression process<u>, which</u> <u>corresponds</u> ~~corresponding~~ to the header compression process in the header compressing part, to the header-compressed packet obtained from the assembling part <u>in order</u> to ~~decompress~~ <u>restore an</u> [[the]] original packet.

Claim 15 (currently amended): A packet transmitting/receiving apparatus comprising a transmitting part and a receiving part for transmitting and receiving packets classified according to a QoS requirement respectively, wherein,

the transmitting part comprises:

a first pre-scheduling part for selecting classes having high priority for transmission from QoS classes specified for data type packets;

a second pre-scheduling part for selecting classes having high priority for transmission from QoS classes [[not]] specified for ~~data type~~ <u>real time</u> packets;

a first dividing part for dividing a queued packet to be transmitted<u>, which</u> <u>belongs</u> ~~belonging~~ to the QoS class selected by the first pre-scheduling part, into a plurality of predetermined data units;

a second dividing part for dividing a queued packet to be transmitted<u>, which</u> <u>belongs</u> ~~belonging~~ to the QoS class selected by the second pre-scheduling part, into a plurality of the predetermined data units;

a transmitter-side retransmission control part for applying a transmitter-side retransmission control process to the packet to be transmitted to be divided by the first dividing part; and

a scheduling part for selecting either one of the QoS classes specified for data type packets or one of the QoS classes [[not]] specified for ~~data type~~ <u>real time</u> packets to be

transmitted, <u>for</u> transmitting the data unit obtained from the transmitter-side retransmission

control part when the QoS class specified for data type packets is selected, and <u>for</u>

transmitting the data unit obtained from the second dividing part when the QoS class [[not]]

specified for ~~data type~~ <u>real time</u> packets is selected, and

the receiving node comprises:

a receiver-side retransmission control part for applying a receiver-side

retransmission control process ~~in each QoS class~~ to the data unit that belongs to one of the

QoS classes specified for data type packets and is one of the received data units;

an assembling part for assembling in each QoS class [[the]] <u>some</u> data units <u>of</u>

<u>the received data units, which</u> [[that]] belong to one of the QoS class [[not]] specified for ~~data~~

~~type~~ <u>real time</u> packets ~~and are some of the received data units~~, and the data units <u>obtained</u>

<u>from the receiver-side retransmission control part, whcih</u> [[that]] belong to one of the QoS

classes specified for data type packets ~~and are obtained from the receiver-side retransmission~~

~~control part,~~ <u>in order</u> to ~~decompress~~ <u>restore an</u> [[the]] original packet,

the receiver-side retransmission control part generates a retransmission request

control signal to indicate a data unit requested to be retransmitted to another packet

transmitting/receiving apparatus communicating with the packet transmitting/receiving

apparatus,

the scheduling part performs a scheduling process on the retransmission

request control signals with the data unit to be transmitted,

the transmitting part further comprises the classifying part for classifying and

outputting the retransmission request control signals transmitted from the opposing packet

transmitting/receiving apparatus into the transmitter-side retransmission control part, and

the transmitter-side retransmission control part outputs to the scheduling part

the data unit indicated by the retransmission request control signal transmitted from the

14

opposing packet transmitting/receiving apparatus upon the retransmission request control signal being input.

Claim 16 (currently amended): The packet transmitting/receiving apparatus as claimed in claim 15, wherein:

the transmitting part further comprises a header compressing part for applying a header compression process in a predetermined manner to the packet to be transmitted;

the receiving part further comprises a header decompression part;

the dividing part divides a header-compressed packet obtained from the header compressing part into a plurality of the predetermined data units;

the assembling part applies the assembling process to the plurality of the predetermined data units in order to decompress the header-compressed packet; and

the header decompression part applies a header decompression process, which corresponds corresponding to the header compression process in the header compressing part, to the header-compressed packet obtained from the assembling part in order to decompress restore an [[the]] original packet.

Claim 17 (currently amended): A packet transmitting/receiving apparatus comprising a transmitting part and a receiving part for transmitting and receiving packets classified according to a QoS requirement respectively, wherein,

the transmitting part comprises:

a first scheduling part for determining transmission order for packets to be transmitted;

a dividing part provided for each QoS class for dividing the packets to be transmitted, of which transmission order is determined by the first scheduling part, into a plurality of predetermined data units in each QoS class;

a transmitter-side retransmission control part for applying a transmitter-side retransmission control process ~~in each QoS class~~ to the data unit that belongs to one of QoS classes specified for data type packets and is one of the data units obtained from the dividing part; and

a scheduling part for selecting a data unit to be transmitted from a set of data units including a data unit that belongs to one of QoS classes [[not]] specified for ~~data type~~ <u>real time</u> packets and is obtained from the dividing part, and a data unit that belongs to one of the QoS classes specified for data type packets and is obtained from the transmitter-side retransmission control part, according to the QoS requirement, and <u>for</u> transmitting the selected data unit,

the receiving part comprises:

a receiver-side retransmission control part for applying a receiver-side retransmission control process ~~in each QoS class~~ to the data unit that belongs to one of the QoS classes specified for data type packets and is one of the received data units;

an assembling part for assembling in each QoS class [[the]] <u>some</u> data units <u>of</u> <u>the received data units, which</u> [[that]] belong to one of the QoS classes [[not]] specified for ~~data type~~ <u>real time</u> packets ~~and are some of the received data units~~, and the data units <u>obtained from the receiver-side retransmission control part, which</u> [[that]] belong to one of the QoS classes specified for data type packets ~~and are obtained from the receiver-side~~ ~~retransmission control part,~~ <u>in order</u> to ~~decompress~~ <u>restore an</u> [[the]] original packet,

the receiver-side retransmission control part generates a retransmission request control signal to indicate a data unit requested to be retransmitted to another packet transmitting/receiving apparatus communicating with the packet transmitting/receiving apparatus,

the scheduling part performs a scheduling process on the retransmission

request control signals with the data unit to be transmitted,

the transmitting part further comprises:

the classifying part for classifying and outputting the retransmission request

control signals transmitted from the opposing packet transmitting/receiving apparatus into the

transmitter-side retransmission control part, and

the transmitter-side retransmission control part outputs to the scheduling part

the data unit indicated by the retransmission request control signal transmitted from the

opposing packet transmitting/receiving apparatus upon the retransmission request control

signal being input.

Claim 18 (currently amended): The packet transmitting/receiving apparatus as

claimed in claim 17, wherein:

the transmitting part further comprises a header compressing part for applying a

header compression process in a predetermined manner to the packet to be transmitted;

the receiving part further comprises a header decompression part;

the dividing part divides a header-compressed packet obtained from the header

compressing part into a plurality of the predetermined data units;

the assembling part applies the assembling process to the plurality of the

predetermined data units in order to decompress the header-compressed packet; and

the header decompression part applies a header decompression process, which

corresponds corresponding to the header compression process in the header compressing part,

to the header-compressed packet obtained from the assembling part in order to decompress

restore an [[the]] original packet.

Claim 19 (currently amended): A packet transmitting apparatus for transmitting packets classified according to a QoS requirement, the packet transmitting apparatus comprising:

a dividing part provided for each QoS class for dividing a packet to be transmitted into a plurality of predetermined data units in each QoS class;

a transmitter-side retransmission control part for applying a transmitter-side retransmission control process in each QoS class to the data unit that belongs to one of QoS classes specified for data type packets and is one of the data units obtained from the dividing part; and

a scheduling part for selecting a data unit to be transmitted from a set of data units including a data unit that belongs to one of QoS classes [[not]] specified for data type real time packets and is obtained from the dividing part, and a data unit that belongs to one of the QoS classes specified for data type packets and is obtained from the transmitter-side retransmission control part, and for transmitting the selected data unit.

Claim 20 (original): The packet transmitting apparatus as claimed in claim 19, wherein:

the packet transmitting apparatus further comprises a header compressing part for applying a header compression process in a predetermined manner to the packet to be transmitted; and

the dividing part divides a header-compressed packet obtained from the header compressing part into a plurality of the predetermined data units.

Claim 21 (currently amended): A packet transmitting apparatus for transmitting packets classified according to a QoS requirement, the packet transmitting apparatus comprising:

a first pre-scheduling part for selecting classes having high priority for transmission from QoS classes specified for data type packets;

a second pre-scheduling part for selecting classes having high priority for transmission from QoS classes [[not]] specified for ~~data type~~ real time packets;

a first dividing part for dividing a queued packet to be transmitted, which belongs ~~belonging~~ to the QoS class selected by the first pre-scheduling part, into a plurality of predetermined data units;

a second dividing part for dividing a queued packet to be transmitted, which belongs ~~belonging~~ to the QoS class selected by the second pre-scheduling part, into a plurality of the predetermined data units;

a transmitter-side retransmission control part for applying a transmitter-side retransmission control process to the packet to be transmitted to be divided by the first dividing part; and

a scheduling part for selecting either one of the QoS classes specified for data type packets or one of the QoS classes [[not]] specified for ~~data type~~ real time packets to be transmitted, for transmitting the data unit obtained from the transmitter-side retransmission control part when the QoS class specified for data type packets is selected, and for transmitting the data unit obtained from the second dividing part when the QoS class [[not]] specified for ~~data type~~ real time packets is selected.

Claim 22 (original): The packet transmitting apparatus as claimed in claim 21, wherein:

the packet transmitting apparatus further comprises a header compressing part for applying a header compression process in a predetermined manner to the packet to be transmitted;

19

the dividing part divides a header-compressed packet obtained from the header compressing part into a plurality of the predetermined data units.

Claim 23 (currently amended): A packet transmitting apparatus for transmitting packets classified according to a QoS requirement, the packet transmitting apparatus comprising:

a first scheduling part for determining transmission order for packets to be transmitted;

a dividing part provided for each of QoS class for dividing the packets to be transmitted, of which transmission order is determined by the first scheduling part, into a plurality of predetermined data units in each QoS class;

a transmitter-side retransmission control part for applying a transmitter-side retransmission control process in each QoS class to the data unit that belongs to one of QoS classes specified for data type packets and is one of the data units obtained from the dividing part; and

a scheduling part for selecting a data unit to be transmitted from a set of data units including a data unit that belongs to one of QoS classes [[not]] specified for data type real time packets and is obtained from the dividing part, and a data unit that belongs to one of the QoS classes specified for data type packets and is obtained from the transmitter-side retransmission control part, according to the QoS requirement, and for transmitting the selected data unit.

Claim 24 (original): The packet transmitting apparatus as claimed in claim 23, wherein:

the packet transmitting apparatus further comprises a header compressing part for applying a header compression process in a predetermined manner to the packet to be transmitted;

20

the dividing part divides a header-compressed packet obtained from the header compressing part into a plurality of the predetermined data units.

Claim 25 (currently amended): A packet receiving apparatus for receiving packets classified according to a QoS requirement in the form of predetermined data units into which the packets are divided, the packet receiving apparatus comprising:

a receiver-side retransmission control part for applying a receiver-side retransmission control process ~~in each QoS class~~ to the data unit that belongs to one of the QoS classes specified for data type packets and is one of the received data units;

an assembling part for assembling in each QoS class [[the]] some data units of the received data units, which [[that]] belong to one of the QoS classes [[not]] specified for ~~data type~~ real time packets ~~and are some of the received data units~~, and the data units obtained from the receiver-side retransmission control part, which [[that]] belong to one of the QoS classes specified for data type packets ~~and are obtained from the receiver-side retransmission control part,~~ in order to ~~decompress~~ restore an [[the]] original packet.

Claim 26 (currently amended): A packet receiving apparatus for receiving packets classified according to QoS requirement in the form of predetermined data units into which the packets are processed for header compression and divided, the packet receiving apparatus comprising:

a receiver-side retransmission control part for applying a receiver-side retransmission control process ~~in each QoS class~~ to the data unit that belongs to one of the QoS classes specified for data type packets and is one of the received data units;

an assembling part for assembling in each QoS class [[the]] some data units of the received data units, which [[that]] belong to one of the QoS classes [[not]] specified for ~~data type~~ real time packets ~~and are some of the received data units~~, and the data units obtained from the receiver-side retransmission control part, which [[that]] belong to one of the QoS

21

classes specified for data type packets ~~and are obtained from the receiver-side retransmission control part,~~ in order to decompress the header-compressed packet; and

a header decompression part for applying a header decompression process to the header-compressed packet obtained from the assembling part in order to ~~decompress~~ restore an [[the]] original packet.